

## **RRC-250 & RRC-330 Reel-to-Reel Counting Systems**


The new **RRC-250 and RRC-330 Reel-to-Reel Counting Systems** brings you new convenience in a self-contained table-top Label Counting System using a pre-set counter. For applications where your maximum roll size is 250mm (9.8") or less, and your label width is 152mm (6") or less, the **RRC-250** is a great choice for your label counting needs. For bigger rolls, the **RRC-330** accepts rolls with a maximum size of 330mm (13"). The optional built-in encoder allows length measurement and offers direct read-out in Metric or British & American Units.

**RRC-250:** Accepts roll with a maximum outer diameter of 250mm and 76mm core diameter (other core diameters available on-demand).

**RRC-330:** Accepts roll with a maximum outer diameter of 330mm. Take-up core is available both in Standard and Adjustable Core Holder. The **Standard** take-up shaft is available is 38, 40, 44, 70 and 76mm. The **ACH** (Adjustable Core Holder) accepts cores from 25 to 101mm. The supply core is supplied in both 40mm and 76mm (other core diameters available on-demand).

Designed for all-day, every-day use, the **RRC-250 & RRC-330 Reel-to-Reel Counting Systems** are backed by LABELMATE's famous 3-Year Parts and Labor Limited Warranty, assuring you trouble-free performance.

**IMPORTANT NOTE:** *The RRC can not be used for transparent labels.*



**RRC-250**



**RRC-330**

See Page 2 for available models and specifications.

**"RRC" Reel-to-Reel Counting Systems and Options**

MODEL	ADD SUFFIX	DESCRIPTION	LABEL WIDTH (mm)	ROLL DIAM. (mm)	SPEED*
RRC-250	-	Self-contained Counter System with 90-250VAC, 50-60Hz, 60VA Universal Power Supply. Supply core and take-up shaft diameter 40 & 76mm (other diameters available on demand).	152	250	Min.: 65cm/sec
RRC-330	STANDARD	Self-contained Counter System with 90-250VAC, 50-60Hz, 60VA Universal Power Supply. 40 & 76mm for the supply core and take-up shaft, (other diameters on demand).	152	330	Min.: 65cm/sec
	ACH	Self-contained Counter System with 90-250VAC, 50-60Hz, 60VA Universal Power Supply. 40 & 76mm for the supply core. Adjustable Core Holder (25mm to 101mm) for the take-up shaft.	152	330	Min.: 65cm/sec

\* Minimum speeds are specified with a 76mm take-up core.

**RRC-250 & RRC-330 REEL-TO-REEL COUNTING SYSTEMS OPTIONS**

MODEL	DESCRIPTION	LABEL WIDTH (mm)
ENC	Optional built-in encoder for length measurement. Resolution: RRC-250: 3.5mm RRC-330: 4.4mm Direct read-out in Metric or British & American Units.	-

\* Minimum speeds are specified with a 76mm take-up core.

Specifications are subject to change without notice. DataRRC250-330\_Eur 07/2008