

Specifications LX810 Label Printer

Print Method:	Inkjet
Print Resolutions:	4800 x 1200 dpi, 2400 x 1200 dpi, 600 x 600 dpi
Print Speeds:	Approximately 2" (51mm) per second for black Approximately 1.5" (38mm) per second for color + black Approximately 10" per second feed rate
Ink Cartridges:	PRI53335 Color (CMY) PRI53336 Black Dye-Based (Kd) PRI53020 Black Pigment-Based (Kp)
Colors:	16.7 million
Color Matching:	Z-Color™ Color Matching Software integrated in printer driver
Min. Print Width:	0.75" (19mm)
Max. Print Width:	8.25" (210mm)
Min. Print Length:	0.75" (19mm)
Max. Print Length:	24" (609mm)
Media Types:	Roll-fed pressure-sensitive labels, roll-fed tags
Media Sensing:	Moveable see-through sensor for die-cut labels and reflective for tags with black stripe sensing; Continuous feed.
Supply Roll:	6" (152mm) maximum diameter on 3" (76mm) core
Ink Level Warning:	Calculates actual number of prints remaining based upon ink usage of graphics being printed (patent-pending)
Indicator Lights:	Power, Pause, Ink
Controls:	Pause, Feed, Stop/Cancel
Operating Systems:	Windows XP/2000 or Mac OS X (v. 10.2 or higher)
Data Interface:	USB 2.0
Minimum System:	For PC: Pentium® IV computer or better, 512MB RAM, 5GB free hard drive space, USB 2.0 (recommended) For Mac: 700 MHz G4 or higher with 512MB RAM, 5GB free hard drive space, USB 2.0 (recommended)
Label Design Software:	NiceLabel® SE Primera Edition included. Can also be used with most other popular label design software programs

Electrical Rating: 12VDC, 5.0A

Power Requirements: 100-240VAC, 50/60 Hz, 60 watts

Certifications: UL, UL-C, CE, FCC Class B

Weight: 29 lbs. (13.2 Kg)

Dimensions: 17"W x 9.1"H x 15.5"D (432mmW x 231mmH x 394mmD)